



Technical Specification



Sweeper with polypropylene bristles to clean and collect dust on all surfaces, both in and outdoor.

Frame with **360° pivoting front wheels**.







Collection bucket with tilt hydraulic cylinder.

Easy matching with machines like skid loaders, articulated wheel loaders, fork lifts, telescopic handlers, etc.

Fully hydraulic, including collection bucket opening. **Excellent sweeping** thanks to the **floating linkage** copying the ground.

Sprinkler with water tank, 12V electric pump and nozzles to pulverize water (on request).

Industrial sweeper

MODEL		SI 1200	SI 1500	SI 1800	SI 2100	SI 2200	SI 2400	
Technical specification	um							
Working width	mm	1200	1500	1800	2100	2200	2400	
Overall width	mm	1345	1645	1945	2245	2405	2605	
Oil flow, min-max	lt/min	25-50	25-60	40-80		70-120	100-120	
Oil pressure, min-max	bar	120-200		160-200		200-240		
Weight standard configuration	kg	350	400	460	490	740	800	
Best broom speed	rpm	120						
Broom ring	Ø mm	580 x n. 38	580 x n. 49	580 x n. 59	580 x n. 69	650 x n. 73	650 x n. 79	
Water tank capacity ⁽¹⁾	lt	100						
Collection bucket capacity	lt	230	290	350	410	530	580	
	ton	2,0-2,6	2,4-3,5	3,0-4,0	3,8-5,0	–	–	
	ton	2,0-3,0	2,0-4,0	3,5-5,0	4,5-7,0	–	–	
	ton	2,2-3,5	3,2-4,5	4,0-5,5	4,6-6,8	5,8-8,5	7,5-12,0	
	ton	2,4-3,8	3,4-5,0	4,5-6,0	5,6-7,5	7,0-9,0	8,0-10,0	
	ton	–	–	4,0-5,0	4,5-6,0	5,8-8,5	7,5-12,0	
	Overall size in standard configuration	A cm B cm C cm	135 81 154	165 81 154	195 81 154	225 81 154	240 89 182	260 89 182

⁽¹⁾ Optional

Collection bucket with tilt hydraulic cylinder



Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.