

LB



Technical Specification



Leveling blade to prepare ground for roads, yards, sport grounds.

Right and Left **hydraulic blade** tilt with solenoid valves.

High stability during any job conditions, thanks to **back support skid** hydraulically driven.





Proportional hydraulic valves, with **high precision**.

Compatibility with all **automatic laser systems**.

Predisposition kit for most popular laser brands (optional).

Fixed and removable **lateral wings** for containment of the material .

Leveling blade

MODEL		LB 220	LB 240
Technical specification	um		
Blade width	mm	2200	2400
Oil flow, min-max	lt/min	20-80	
Oil pressure, min-max	bar	140-250	
Weight standard configuration	kg	825	860
Solenoid valve, blade tilt and adjustment skid		proportional	
	ton	3,5-5,5	
	ton	4,2-7,8	
	ton	4,8-8,2	
	Overall size in standard configuration	A cm B cm C cm	222 98 75
			242 98 75



Data, descriptions and images of this document are not binding hence GF Gordini reserves the right to alter part or all of them at any time with no notice.



Ajashy Engineering Sales Private Limited

1505-1506, Tower 4, 15th Floor, DLF Corporate Greens,
Southern Peripheral Road, Sector-74 A, Gurugram, Haryana, India - 122004

Fixed Lines: 0124-5181505/06 | +91-9311666631 Email: info@ajashy.com Web: www.ajashy.com

